



DESIGN STUDIO


Construction / Performance	EN ISO 10582	Heterogeneous PVC No Bevel
Total Thickness	EN ISO 24346	2mm
Wear Resistance	EN 660-2	T
Surface Treatment		PUR
Wear Layer Thickens	EN ISO 24340	0.3mm
Plank Size		180mm x 1200mm Stone 300mm x 600mm
Quantity Per Box – Planks/Tiles		Plank 22 in box (4.75sqm) Stone 27 in box (4.86sqm)
Classification	EN 685	Class 23/31
Straightness and Squareness	EN ISO 24342	0.35mm
Dimensional Stability	EN 750 23999	<0.25
Curling	EN 750 23999	<2
Wear Performance	EN 685	Class 23/31
Castor Chair Test	EN ISO 4918	No Change
Impact Sound Insulation	EN ISO 10140	
Thermal Resistance	EN 1266L	
Chemical Resistance	EN ISO 26987	No Change
Slip Resistance	DIN 51130	R9
Residual Indentation	EN ISO 24343-1	<0.10mm
Underfloor Heating Suitability		
Colour Fastness To Light	EN ISO 105 B02	>6
Flammability	BS EN 13501-1	Bfl-s1

Suitability

- . Hospitality
- . Corporate
- . Education
- . Residential
- . Public Spaces
- . Retail

Guarantee

10 Year Heavy Commercial Wear



JHS RSS 2.0



2009/533

JOSEPH HAMILTON & SEATON

RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401

EMAIL: sales@jhscarpets.com