



DESIGN WORKS STONE

Construction / Performance	EN ISO 10582	PVC Heterogeneous
Surface Treatment		PUR
Plank Size		300mm x 600mm
Quantity Per Box – Planks/Tiles		22 tiles per box 3.96m ²
Straightness and Squareness	EN ISO 24342	<0.35%
Classification	EN 685	Class 23/33/42
Overall Thickness	EN ISO 24346	2.5mm
Wear Layer Thickness	EN ISO 24340	0.55mm
Wear Resistance	EN 660-2	T
Residual Indentation	EN ISO 24343-1	<0.1mm
Dimensional Stability	EN ISO 23999	<0.25%
Curling	EN ISO 23999	<2mm
Castor Chair	EN ISO 4918	No Change
Impact Sound Insulation	EN ISO 10140	2db
Thermal Resistance	EN 12664	0.0092m ² /kw
Chemical Resistance	EN ISO 26987	No Change
Slip Resistance	DIN 51130	R9 – 36+
Underfloor Heating		Suitable 27°C
Colour Fastness To Light	EN ISO 105 B02	<6
Flammability	BS EN 13501-1	Bfl-s1

Suitability

- . Hospitality
- . Corporate
- . Education
- . Residential
- . Public Spaces
- . Retail

Guarantee

10 Year Heavy Commercial Wear



JHS RSS 3.0



2009/533

JOSEPH HAMILTON & SEATON

RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401

EMAIL: sales@jhscarpets.com