



FASTRACK CORD

Construction		Rib-Fibre Bonded
Pile Content		80% Polypropylene 20% Nylon
Primary Backing		Latex
Secondary Backing		
Width		2m
Average Roll Length		30.00m
Pile Weight		800g/m ²
Total Weight		1000g/m ²
Pile Height		2.8mm
Total Height		5.8mm
Gauge		

Performance Classification		LC2
Wear Classification	BS EN 1307	
Tog Rating		0.4
Impact Noise Rating	BS EN ISO 140-8	
Acoustic Insulation	BS EN ISO 717-1	
Static Electricity (Waking Test)	ISO 6356: 2000	
Colour Fastness - Light	BS EN ISO 105 – B02	
Wet Rubbing	BS EN ISO 105 – B01	
Dry Rubbing	BS EN ISO 105 X 12	
Anti-Microbial Treatment		
Thermal Conductivity	BS EN ISO 354	
Flammability	BS EN13501-1	Efl-s1
Hot Metal Nut Test	BS 4790	

Suitability

- . Education
- . Commercial
- . Retail
- . Social Housing
- . Student Accommodation

Guarantee

- . 7 Year Wear

Apply for full details of conditions and limits of above

JHS RSS 1.0



2009/533

JOSEPH HAMILTON & SEATON

RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401

EMAIL: sales@jhscarpets.com