



RIMINI TILE

Construction		Loop Pile
Pile Content		100% Polypropylene
Primary Backing		Non-Woven Nylon
Secondary Backing		Bitumen with glass fibre
Tile Size		50cm x 50cm
Pile Weight		390g/m ²
Total Weight		4235g/m ²
Pile Height		2.5mm
Total Height		6.0mm
Number Of Tiles Per Box		

Performance Classification	BS EN 1307	
Castor Chair	BS EN 985 PARTA	
Impact Noise Rating	BS EN ISO 140-8	
Acoustic Insulation	BS EN ISO 717-1	
Static Electricity (Walking Test)	ISO 6356 : 2000	<2kv
Colour Fastness - Light	BS EN ISO 105 B02	6
Wet	BS EN ISO 105 B01	4-5
Dry Rubbing	BS EN ISO 105 x 12	4-5
Anti-Microbial Treatment		
Thermal Resistance	BS EN ISO 8301	
Flammability	BS EN 13501-1	Cfl-s1
Hot Metal Nut Test	BS 4790	Low Radius of Ignition

Suitability

- . Commercial
- . Retail
- . Hospitality
- . Office

Guarantee

5 Year Wear

Apply for full details of conditions and limits of above



JHS RSS 2.0



2009/533

JOSEPH HAMILTON & SEATON
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152

J O S E P H
H A M I L T O N
& S E A T O N



FITTING INSTRUCTIONS

Important Installation Information which MUST BE adhered to.

This product has been produced according to strict quality control standards and will provide years of trouble-free service provided that it is properly fitted and maintained.

The carpet tiles should be installed in accordance with 855325 Code of Practice for the Installation of Textile Floorcovering. Subfloors must be smooth, hard, clean, dry and free of dust before laying. Uneven, solid or suspended timber subfloors may need preparation to meet the required standard. An efficient DPM must be incorporated in direct-to-earth concrete subfloors.

Tiles to be used in the same room/area should be from the same dye batch (indicated on the lid of the box). They should be unpacked and allowed to acclimatise at a minimum of 18°C for at least 48 hours before installation. During winter months (Oct to Mar) 72 hours acclimatising should be allowed. Relative humidity should not be more than 75%. As a precaution against extremes of temperature and humidity (especially in new buildings) we recommend the use of an all-over tackifier such as F. Ball's F41. For expert advice on adhesives, please refer to F. Ball & Co. Limited of Leek, Staffordshire, telephone number 01538 361633.

Where tiles are used in conjunction with chair castors some flattening of the pile will occur and it is therefore essential to use keyhole mats to protect the surface pile of the carpet. Castor cups should be used under heavy point loads.

NON DIRECTIONAL - Tiles installed without regard to direction or orientation.

No arrow to indicate tile direction. The above acclimatising instructions must be adhered to.

FOR STRIPES - Strictly chequerboard installation only (laying direction is indicated via an arrow on the back of each tile). The above acclimatising instructions must be adhered to.

MAINTENANCE

Regular maintenance of carpet tiles is essential to prolong the useful life of the carpet. Dirt barrier carpeting should always be used adjacent to entrances. Daily routine should include spot removal and thorough vacuum cleaning with a commercial upright cleaner, preferably with a power driven brush head. Regular maintenance should be via bonnet buffing or rotary pad skimming, with periodic deep cleaning via water extraction or rotary shampoo.



2009/533

JOSEPH HAMILTON & SEATON
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152