

J O S E P H
H A M I L T O N
& S E A T O N



SAFETY TECH & SAFETY TECH CHIP

Construction	Compact Heterogeneous	
Total Thickness	2.0mm	
Wear Layer Thickness	0.7mm	
Width	2m	
Total Weight	2,400g/m ²	
Wear Classification	EN ISO 10874	class 34/43
Abrasion Group	EN 660-1	Group T
Residual Indentation	EN ISO 24343	max 0.1mm
Dimensional Stability	EN ISO 23999	max 0.2%
Fire Resistance	EN 13501-1	Class: Bfl-s1
Slip Resistance	EN 13893 EN 13893	Class DS RRL Pendulum test – Low slip potential (wet test) ≥36
Light Fastness	EN ISO 105-B02	Grade 6
Castor Chair Resistance	A Continuous	
Surface Treatment	TechSurface	
Anti-Bacterial And Fungicide Treatment	Silver Knight	
Seaming Method	Hot or cold weld	

Guarantees: 10 years heavy commercial

Full details of conditions and limits of guarantees available on request.



2009/533

JOSEPH HAMILTON & SEATON

RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401

EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152