



**SAFETY PLUS TIMBER**

Construction	<b>EN 649</b>	Safety Flooring Heterogeneous PVC
Slip Classification	<b>EN13845</b>	Class ESf & ESb
Slip Restraint	<b>DIN 51130</b>	R11- low potential of slip
Abrasion Resistance	<b>EN13845</b>	<10% particles lost over 50,000 cycles
RRL Pendulum Test	<b>RRL</b>	36+
Surface Roughness		RZ ≥ 20µm low slip potential
Wear Layer	<b>EN ISO 24340</b>	0.70mm
PUR Wear Layer Treatment		Hyper grip
Width		2m & 4m
Total Thickness	<b>EN ISO</b>	2.00mm
Total Weight	<b>EN ISO 23997</b>	2850gm2
Standard Roll Length		20m
Wear Classification	<b>EN ISO 10874</b>	30 – 43
Electrical Resistance	<b>EN ISO 10965</b>	10 <sup>9</sup> ohm
Static Electrical Propensity	<b>EN 1815</b>	≤ 2kV
Chemical Resistance	<b>EN ISO 26987</b>	Very good
Residual Indentation	<b>EN ISO 24343-1</b>	0,04mm
Furniture Leg Resistance	<b>EN ISO 16581</b>	Very Good
Acoustic Insulation	<b>ISO 717-2</b>	7db
Curling	<b>EN ISO 23999</b>	≤ 8mm
Castor Chair	<b>EN ISO 4918</b>	Very Good
Underfloor Heating	<b>EN 12524</b>	Suitable
Cold Welding		Suitable
Abrasion Group	<b>ISO 10582</b>	Type I
VOC Emissions		Low VOC
Fire Classifications	<b>BS EN13501-1</b>	Bfl-s1

**Suitability**

- . Commercial
- . Retail
- . Hospitality
- . Office

**Guarantee**

**5 Year Heavy Commercial Wear**



2009/533

**JOSEPH HAMILTON & SEATON**

RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401

EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152