



SUPA-LOCK TILE

Description: Loose lay interlocking floor tile (non-ESD)

Construction	PVC compound
Tile Size	7mm: 500x500mm T-Joint (10 tiles per pack)
VOC Content	Trace elements of volatiles from modifiers and non PVC based additives. Significantly lower VOC levels when compared to resin based flooring systems or the levels encountered when using adhesives to stick down conventional floor coverings. Supa-lock contains no formaldehyde and carries a class E1 rating.
Sustainability	Supa-lock is 100% recyclable, at the end of its service life the tiles can be granulated and re-used to manufacture a new floor.
Weight	7mm: 8.86kg/m ²
Hardness	89 - 92 shore A
Thickness	BS EN 428 – 4.5 to 9.24mm +/- 0.15mm
Abrasion Wear	BS EN 660-2 / En 13845 Wear Group T (<0.1mm /100 revs)
Mechanical Resistance	17 N/mm ² to DIN 53516

Test Results:

Fire Class	Class 1 BS 476: Part 7 / DIN 13501: 2004 – Bfl-S1
Electrical Properties	Resistance to ground : 5.7 x 10 ⁵ Ω and 2.9 x 10 ⁴ Ω
Anti Slip	R10
Chemical Resistance	Good - EN 13529 – Common acids oils & gas oil – No deterioration Solvents – Not resistant to prolonged contact.
Determination of Residual Indentation	BS EN 433:1994 <0.1mm /Dimensional Stability – BS EN 434:1994 – Maximum change in dimension <0.1% / Compressive Strength – ISO 6721-1:1994, ISO 6721-2:1994, ISO 6721-6:1996: 520kg/cm ²
Colour Fastness /Resistance to natural light	EN 20105-B021 – 5 (no damage)
Sound Absorption	Noise reduction of up to 46db can be achieved

Can be used on under floor heating, but tiles must be acclimatised first.

Guarantees:

- 20 year heavy commercial wear
- Full details of conditions and limits available on request



2009/533

JOSEPH HAMILTON & SEATON
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152