

# J O S E P H H A M I L T O N & S E A T O N



## TRIUMPH RANDOM

<b>Construction</b>		Loop Pile Tile
<b>Pile Content</b>		100% Solution Dyed Nylon
<b>Primary Backing</b>		Non-Woven Polypropylene
<b>Secondary Backing</b>		Bitumen
<b>Tile Size</b>		50cm x 50cm
<b>Pile Weight</b>		500g/m <sup>2</sup>
<b>Total Weight</b>		4300g/m <sup>2</sup>
<b>Pile Height</b>		3.5mm
<b>Total Height</b>		7.2mm
<b>Number Of Tiles Per Box</b>		20

<b>Wear Classification</b>		33
<b>Luxury Class</b>		LC1
<b>Castor Chair</b>	BS EN 985 PARTA	
<b>Impact Noise Rating</b>	BS EN ISO 140-8	
<b>Acoustic Insulation</b>	BS EN ISO 717-1	
<b>Static Electricity (Walking Test)</b>	ISO 6356 : 2000	Less than 2kv
<b>Colour Fastness - Light</b>	BS EN ISO 105 B02	4-5
<b>Wet</b>	BS EN ISO 105 B01	4-5
<b>Dry Rubbing</b>	BS EN ISO 105 x 12	5
<b>Thermal Resistance</b>	BS EN ISO 8301	
<b>Flammability</b>	BS EN 13501-1	Cfl-s1
<b>Hot Metal Nut Test</b>	BS 4790	Low radius of ignition

### Suitability

- . Commercial
- . Retail
- . Hospitality
- . Offices

### Guarantee

- 10 Year Heavy Commercial Wear
- 10 Year Anti Shock



2009/533

**JOSEPH HAMILTON & SEATON**  
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401  
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152

J O S E P H  
H A M I L T O N  
& S E A T O N



## FITTING INSTRUCTIONS

Important Installation Information which MUST BE adhered to.

This product has been produced according to strict quality control standards and will provide years of trouble-free service provided that it is properly fitted and maintained.

The carpet tiles should be installed in accordance with 855325 Code of Practice for the Installation of Textile Floorcovering. Subfloors must be smooth, hard, clean, dry and free of dust before laying. Uneven, solid or suspended timber subfloors may need preparation to meet the required standard. An efficient DPM must be incorporated in direct-to-earth concrete subfloors.

Tiles to be used in the same room/area should be from the same dye batch (indicated on the lid of the box). They should be unpacked and allowed to acclimatise at a minimum of 18°C for at least 48 hours before installation. During winter months (Oct to Mar) 72 hours acclimatising should be allowed. Relative humidity should not be more than 75%. As a precaution against extremes of temperature and humidity (especially in new buildings) we recommend the use of an all-over tackifier such as F. Ball's F41. For expert advice on adhesives, please refer to F. Ball & Co. Limited of Leek, Staffordshire, telephone number 01538 361633.

**Where tiles are used in conjunction with chair castors some flattening of the pile will occur and it is therefore essential to use keyhole mats to protect the surface pile of the carpet. Castor cups should be used under heavy point loads.**

**NON DIRECTIONAL - Tiles installed without regard to direction or orientation.**

**No arrow to indicate tile direction.** The above acclimatising instructions must be adhered to.

**FOR STRIPES - Strictly chequerboard installation only (laying direction is indicated via an arrow on the back of each tile).** The above acclimatising instructions must be adhered to.

### MAINTENANCE

Regular maintenance of carpet tiles is essential to prolong the useful life of the carpet. Dirt barrier carpeting should always be used adjacent to entrances. Daily routine should include spot removal and thorough vacuum cleaning with a commercial upright cleaner, preferably with a power driven brush head. Regular maintenance should be via bonnet buffing or rotary pad skimming, with periodic deep cleaning via water extraction or rotary shampoo.



2009/533

**JOSEPH HAMILTON & SEATON**  
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401  
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152