



## TWEED & TWEED DESIGN

<b>Construction</b>		Tweed Loop Pile	Tweed Design Loop Pile
<b>Pile Content</b>		100% Imprel Nylon 6	100% Imprel Nylon 6
<b>Primary Backing</b>		Woven Polypropylene	Woven Polypropylene
<b>Secondary Backing</b>		Action	Action
<b>Width</b>		4m & 5m	4m & 5m
<b>Average Roll Length</b>		30.00lm	30.00lm
<b>Pile Weight</b>		660g/m <sup>2</sup>	680g/m <sup>2</sup>
<b>Total Weight</b>		1750g/m <sup>2</sup>	1790g/m <sup>2</sup>
<b>Pile Height</b>		3mm	4mm
<b>Total Height</b>		6mm	6mm
<b>Gauge</b>		1/10th	1/10 <sup>th</sup>

<b>Performance Classification</b>		LC1	LC1
<b>Wear Classification</b>	BS EN 1307	23 & 32	23 & 32
<b>Luxury Class</b>			
<b>Caster Chair</b>	BS EN 985 PARTA	A - Intensive use	A – Intensive use
<b>Impact Noise Rating</b>	BS EN ISO 140-8	22db	22db
<b>Sound Absorption</b>		0.20aw	0.20aw
<b>Static Electricity (Waking Test)</b>	ISO 6356: 2000	<2kv	<2kv
<b>Tog Rating</b>		1.1	1.1
<b>Colour Fastness - Light</b>	BS EN ISO 105 – B02	5-6	5-6
<b>Wet Rubbing</b>	BS EN ISO 105 – B01	4	4
<b>Dry Rubbing</b>	BS EN ISO 105 X 12	4-5	4-5
<b>Thermal Conductivity</b>	BS EN ISO 354		
<b>Stair Suitability</b>	EN 1963	A - Intensive Use	A - Intensive Use
<b>Thermal Resistance</b>	BS EN ISO 8302	0.11m <sup>2</sup> /kw	0.11m <sup>2</sup> /kw
<b>Flammability</b>	BS EN13501-1	Cfl-s1 if glued	Cfl-s1 if glued
<b>Hot Metal Nut Test</b>	BS 4790		

### Suitability

- . Commercial
- . Retail
- . Student Accommodation
- . Leisure

### Guarantee

10 Year Heavy Wear



JHS RSS 1.0



2009/533

**JOSEPH HAMILTON & SEATON**  
RELAY PARK, RELAY DRIVE, TAMWORTH STAFFORDSHIRE, B77 5PR

TELEPHONE: (01827) 831400 TELEFAX: (01827) 831401  
EMAIL: sales@jhscarpets.com

Registered Office: Gorsey Lane Coleshill Birmingham B46 1JU England HFD Ltd Registered in England and Wales No. 2674152